

- Outer casing of varnished steel.
- Roller coated in Polyester.
- Works by means of a pedal.
- Strap feeding.
- Return feed design requires minimum installation space.
- Safety protector for hands.
- Controlled by microprocessor.
- Temperature control by thermostat.
- Safety thermostat.
- Electric heating system.
- Roller diameter Ø 180 mm.
- Roller length: 1.000 mm.
- Speed: 2,02 m/minute.
- Production: 15 kg/h.
- Electrical connection: 230 V 1+N.
- Heating power: 3 kW.
- Electrical power: 3,03 kW.
- Dimensions: 1.280 x 400 x 940 mm.



Entry with 20% ± 25% maximum humidity

# MAXIFINISH

MFI-7-40-M			
Roller Diameter	mm	<b>180</b>	
Roller Length	mm	<b>1,000</b>	
Production	kg/h	<b>15</b>	
<b><u>ELECTRICITY</u></b>			
Electric power	KW	<b>3.03</b>	
230V - 1+N		<b>2x2,5+T-25 A</b>	
230V - III+T			
400V - III+N+T			
<b><u>STEAM</u></b>			
Steam Heating Power		Not used	
Consumption	kg/h	N/A	
Pressure	bar	N/A	
<b><u>AIR</u></b>			
Consumption	NI/min	N/A	
Pressure	kg/cm2	N/A	
<b><u>WATER</u></b>			
Not used			
<b><u>GAS</u></b>			
Not used			
<b><u>LEVEL SOUND</u></b>	(dB)	<b>55,00</b>	
<b><u>DIMENSIONS</u></b>		<u>Article</u>	<u>Packed</u>
Length	mm	<b>1,280.00</b>	<b>1,300.00</b>
Depth	mm	<b>400.00</b>	<b>470.00</b>
Height	mm	<b>940.00</b>	<b>1,090.00</b>
Weight	Kg	<b>74.00</b>	<b>84.00</b>
Volume	m3	<b>0.48</b>	<b>0.66</b>