

Rigid Mount Washer-Extractor

MWCM60
G FORCE = 300 | 25 kg




- **G Force = 300.**
 - Hard-mounted machines. Require anchoring to the floor.
 - Drum and jacket in AISI-304 stainless steel.
 - Unit exterior manufactured in sandwich board, colour grey, stainless steel appearance, easy to clean, and which does not reflect fingerprints.
 - Detergent tray with 4 compartments.
 - 8 signals for automatic liquid dosing, programmable in time and delay. 6 extra signals available optionally.
 - 3 standard water inlets.
 - Variable-frequency drive (standard 50-60 Hz). Balancing systems controlled by the same drive.
 - **TOUCH PLUS programmer**
 - Allows programming, importing and exporting of programs and software updates via USB.
 - Traceability as standard: the whole wash process (temperatures, water levels) is stored on the washer and is extractable to a PC by USB memory.
 - The programmer includes the characteristics to create any Wet Cleaning program (modifiable water levels and washing speed).
 - **EFFICIENT MIX.** These machines are equipped with an automatic water mixer (mixing different water temperatures) which provides energy savings and reduces washing times.
 - **BALANCE CONTROL.** Thanks to an advanced technological development, and by means of the inverter, the washers detect the imbalance at an early stage. This way the operation is much smoother, elongating components lifetime and reducing washing times, thus saving energy as well.
 - **MULTICHOICE INLET.** All washers are equipped with a third water inlet as standard, which allows you to save filling time, or which can be used for decalcified water, ozone or recycled water.
 - **WET CLEANING.** All washers incorporate the necessary features to use the WET CLEANING system as standard, avoiding investment in expensive applications to work with this advanced washing concept. This feature replaces most dry-cleaning washing systems, bringing maximum reduction in costs.
 - **MAINTENANCE KARE.** A simple and reliable design with easy-to-access mechanical parts that combines perfectly with the use of intelligent electronics. All components have been designed and manufactured with top quality and prestige, focusing on optimum accessibility for all points and components key to maintenance. Moreover, all the controls have been developed down to the finest detail: complete technical menus, fault self-diagnosis systems, alarms, restricted access areas, etc.
 - **OPTIMISED DRUM.** This system has been developed to improve wash quality to the maximum and to do it in as short a time as possible. Through a series of perforations in the paddles of the drum, a water cascade effect is achieved which considerably increases the mechanical action inside the drum during operation and greatly reduces the amount of water needed for each wash. The effective design of the drum and tank with minimal spaces between them, allows the energy consumption necessary to heat the water, as well as the superfluous use of chemical products, to be reduced.
 - **OPTIMAL CONSUMPTION** All washers are equipped with an efficient system by means of which you can indicate the load which is introduced in the machine. The washer automatically adapts the quantity of water and chemicals to be used for that load.
 - **“LOADING AID”** system. Water inlet and spin control for loading the linen.
 - The standard model can be converted to self-service by installing a pay station kit, coin mechanism kit or other payment system. RS-485 communication.
 - Washers compatible with water recovery tanks.
 - **CE, WRAS and EAC product certifications.** Optional ETL-certified version of the machine.
- OPTIONS:**
- Anchoring base as an option for correct fixation to the floor.
 - Unit exterior in AISI-304 stainless steel.
 - Front panels in AISI-304 stainless steel.
 - Double drain kit to recover the water, with important savings.
 - NC Option: drain normally closed.
 - Reversible door opening.
 - 6 extra signals for dosing
 - Timed opening system.
 - Printer.
 - Marine electric versions for ships.
 - Tropicalised models with protective covering for the electronics system.
 - Shower system: water recirculation for very delicate linen (wet cleaning complement).

TECHNICAL DATA

	UNIT.	MWCM-60		
DRUM				
Capacidad de carga 1:9 / 1:10	kg	28/25		
Volumen	Lit	250		
Diámetro	mm	770		
Profundidad	mm	530		
GENERAL DATA				
Wash speed / Spin speed	r.p.m.	40/836		
G Force	-	300		
Maximum force transmitted	kN	3.96 ±10		
Dynamic force frequency	Hz	11,5		
Noise level	dB	< 70		
Self-service version	-	Yes		
Double drain	-	Opt.		
Weighing system	-	No		
DOOR				
Height door centre / Height door base	mm	700 / 400		
Diameter	mm	460		
POWER				
Motor	kW	3		
Heating electric mod,	kW	18		
Maximum electrical power	kW	19		
Maximum steam and hot water power	kW	3		
CONNECTIONS				
Voltage 230V - I + N	Nº x mm² / A	-	ELECTRIC	STEAM / HOT WATER
Voltage 230V - III	Nº x mm² / A	4 x 16 / 63 A		3 x 4 / 32 A
Voltage 400V - III + N	Nº x mm² / A	5 x 4 / 32 A		-
Steam inlet (Steam mod,)	inch	3/4"		
Maximum steam consumption (Steam, mod,)	kg/h	15		
Water inlet	inch	3/4"		
Grid pressure	kg/cm²	2-4		
Maximum water consumption *	Lit/h	176.1*		
Drain	mm/inch	3"		
Drainage capacity	Lit/min	200		
DIMENSIONS / DIMENSIONS WITH PACKAGING				
Width / Width	mm	884 / 930		
Depth / Depth	mm	1,011 / 1,150		
Height / Height	mm	1,340 / 1,523		
Net weight / Gross weight	kg	340 / 370		
Gross volume (with packaging)	m³	1.60		

* Program n° 20, 75 % load.



- ① Soap dispenser.
- ② Emergency stop.
- ③ USB port.
- ④ Drain.
- ⑤ Electrical connection to liquid soap pumps.
- ⑥ Electrical connection.
- ⑦ Main switch.
- ⑧ Auxiliary water inlet.
- ⑨ Hot water inlet.
- ⑩ Earth connection.
- ⑪ Cold water inlet.
- ⑫ Water overflow.
- ⑬ Connection for liquid soap.
- ⑭ Steam connection.

	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	CGY	CGZ
MWCM-60	884	1,011	1,340	400	460	145	548	1,063	1,230	1,065	1,250	1,135	61	74	101	428	508	801	639	268	820	771	1,220	600	1,280	543	591