



PROFESSIONAL WASHER EXTRACTORS



01. MORE FEATURES

- New TP2 scheduler with touch screen. It allows to create an indefinite number of programs (26 preestablished).
- Allows programming, importing or exporting programs and software updates via USB.
- Standard traceability: The entire washing process (temperatures, water levels) is stored in the washing machine and can be extracted to a PC via USB memory.
- WET CLEANING included in the scheduler (modifiable water levels and washing speed).
- Wash-Control, PC software for program management, traceability and other data.
- Designed for remote connections.
- Designed for multipayment system.
- 8 programmable automatic liquid dosing signals with timedelay element. With a choice of 6 extra signals.
- Reduced washing cycles (heating power 6 kW).

02. MORE ROBUSTNESS

- Gray skinplate.
- Tank, drum and blades made of AISI 304.
- Robust door made of aluminum.
- Industrial door lock machine door seal (no inner drum seal).
- Industrial housing and bearings.
- Frequency converter and industrial motor.

CHARACTERISTICS

- High spinning washers, not requiring anchoring to the ground.
- Tank with 4 detergent compartments.
- 2 standard water inlets.
- Equipped with a frequency converter (standard 50-60 Hz). Balancing system controlled by the same converter.
- Model with drain valve (V) and model with drain pump (P).
- Model with valve specially designed to wash mops.
- Includes levelers.
- CE and WRAS product certifications.

03. MORE VERSATILITY

- New possibility to customize the machines from factory with the available options.
- OPL ↔ COIN
Convertible models from self-service to OPL and vice versa.
- ONE UNIT ↔ COLUMN
Standard model easily installable in column.
- ELECTRIC ↔ HOT WATER
Standard electric model easily convertible to hot water model and vice versa.
- DRAIN VALVE ↔ DRAIN PUMP
Standard models easily convertible. Easy access for maintenance.

OPTIONS

- Double drain (only valve mode).
- Drain pump kit.
- Drain normally closed "NC". In case of power failure, the water stays inside the tank.
- 6 extra signals for dosing: a total of up to 14 available.
- Silicone door seal.
- Door with opposite opening.
- Delayed door opening, in case of power failure.
- Stainless steel fitment AISI 304.
- Designed for remote connections. (Wifi, Ethernet ...)


04. MORE EFFICIENCY

- Intelligent and manual weighing system. Automatic adjustment of water and chemicals.
- Possibility of configuring three levels of savings.
- High Factor G 450. Reduced residual humidity → Reduces drying time.
- Designed for use with tanks for water recovery.

- Plinth that facilitates access to the machine.
- Special mop plinth (with filter) - valve models only.
- Plinth and water recovery tank.
- Kits for self-service: Central payment, file, wallet.
- Voltage 110 1N 50/60 Hz.
- Voltage 440 3- (No N) 50/60 Hz.

TECHNICAL DATA

	UNID.	MWP8 V	MWP8 P	MWP10 V	MWP10 P
DRUM					
Load capacity (KG) 1:9 / 1:10	Kg	9/8	9/8	11/10	11/10
Volume	l	80	80	100	100
Diameter	mm	532	532	532	532
Depth	mm	360	360	425	425
GENERAL DETAILS					
Washing speed / Spinning speed	r.p.m.	50/ 1.250	50/ 1.250	50/ 1.250	50/ 1.250
G Factor	-	450	450	450	450
Self service version	-	SI	SI	SI	SI
Double drain	-	SI	No	SI	No
Weighing system / tilting system	-	No	No	No	No
DOOR					
Height center door / Height base door	mm	537/280	537/280	537/280	537/280
Diameter	mm	373	373	373	373
DYNAMIC FORCE					
Static Load	KN	1,4	1,4	1,5	1,5
Maximum Dynamic load	KN	0,5	0,5	0,6	0,6
Vertical maximum load	KN	0,64	0,64	0,75	0,75
Max revolutions	r.p.m.	1.250	1.250	1.250	1.250
Frequency of dynamic load	-	18,33	18,33	18,33	18,33
POWER					
Motor	kW	0,75	0,75	0,75	0,75
Electric heating	kW	6	6	6	6
Hot water heating	kW	0	0	0	0
Max. power electric model	kW	6,25	6,25	6,25	6,25
Max. power HW model	kW	0,75	0,75	0,75	0,75
Max. power steam	kW	No	No	No	No
CONNECTIONS					
Water inlet	inch	3/4"	3/4"	3/4"	3/4"
Drain	mm/inch	2"	1" (Bomba)	2"	1" (Bomba)
DIMENSIONS / PACKING DIMENSIONS					
Width / width	mm	680/710	680/710	680/710	680/710
Depth / Depth	mm	698/832	698/832	772/832	772/832
Height / height	mm	1.040/1.130	1.040/1.130	1.040/1.130	1.040/1.130
Net weight / Gross weight	kg	140/150	140/150	140/150	150/160



01. Soap dispenser
02. USB port
03. Drain
04. Main switch
05. Electric connection to liquid soap pumps
06. Electrical connection
07. Liquid soap inlet
08. Cold water inlet
09. Hot water inlet
10. Plinth height 389 mm

	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q
MWP8 V	680	698	1040	278	373	86	964	962	922	944	954	110	366	453	528	603	199
MWP8 P	680	698	1040	278	373	-	964	962	922	944	954	110	366	453	528	603	-
MWP10 V	680	772	1040	278	373	86	964	962	922	944	954	110	366	453	528	603	199
MWP10 P	680	772	1040	278	373	-	964	962	922	944	954	110	366	453	528	603	-