

OPL Tumble Dryers

Features and Benefits

- Stainless steel heater
- Trans-axial air flow (12kgs, 15kgs)
- Variable drum speed (12kgs, 50kgs)
- Up to 10 programs with microprocessor control
- Fully insulated cabinet
- Reversing basket
- Stainless steel basket
- Intuitive micro control with auto dry system (12kgs, 15kgs)
- Extra-large door with full view glass
- Dual time control for drying and cooling
- Inverter Drive System (12kgs, 50kgs)
- Available in steam & electric



Available in the following capacities:
12kg, 15kg, 25kg, 35kg, 50kg and 100kg

PRODUCT SPECIFICATIONS

Model		HG-240	HG-300	HG-500Z/DQ	HG-700Z/DQ	HG-1000Z/DQ	HG-2000ZQ
Capacity	kg	12	15	25	35	50	100
Diameter	mm	740	840	960	960	1200	1448
Depth	mm	488	510	650	1000	870	1180
Door opening	mm	Ø 580	Ø 657	Ø 660	Ø 660	Ø 960	Ø 960
Floor to door	mm	948	1018.5	1050	1050	1158	1290
Main motor power	kW	0.12	0.37	1.1	1.1	1.5	2.2
Blower motor power	kW	0.25	0.37	1.1	1.1	1.1	3
Electric heater power	kW	7.5/12	10/15	30	36	45	/
Steam pressure	MPa	0.3-0.6	0.3-0.6	0.4-0.6	0.4-0.6	0.4-0.6	0.4-0.6
Steam Consumption	kg	45	47	50	60	65	130
Exhaust duct connection	mm	Ø 110	Ø 146.5	Ø 188	Ø 188	Ø 248	273X362
Steam inlet	inch	1/2"	1/2"	G1/2"	R1"	G1"	R1 1/2"
Water outlet	inch	1/2"	1/2"	G1"	R1"	G1"	R1 1/2"
Length	mm	850	1020	1060	1060	1300	1632
Width	mm	880	1020	1200	1350	1490	1880
Height	mm	1650	1980	1980	1980	2200	2524
Net weight	kg	150	220	430	500	640	1000

4317 E. Genesee Street Suite 100 DeWitt, New York 13214 USA
Phone: 315 446-2180 Fax: 315-446-2431
E-mail: sales@maxico.com